

Nio 3MP (E-3620 MA)

3 MegaPixel diagnostic grayscale display system



Nio is Barco's flexible, industry-standard display solution for diagnostic imaging. Nio 3MP provides image crispness and an excellent viewing angle in a 2048 x 1536 resolution.

High-quality imaging

The Nio 3MP brings high brightness, exceptional crispness and an excellent viewing angle to your readings. Backlight Output Stabilization (BLOS) technology guarantees fast power-up and continuously stabilizes the luminance output of the LCD's backlight.

Fully transparent calibration and QA

Barco's Nio 3MP is bundled with MediCal QAWeb for automated DICOM calibration, Quality Assurance, display asset management, problem solving and reporting, guaranteeing maximum diagnostic confidence and uptime of your PACS display systems.

The Nio 3MP display system includes:

- A 3 MegaPixel flat panel display
- MediCal QAWeb software for automated calibration and Quality Assurance
- A high-speed, high-performance display controller: check the compatibility matrix

BARCO

Visibly yours

Technical specifications

Screen technology	TFT AM LCD Dual Domain IPS
Active screen size (diagonal)	528 mm (20.8")
Active screen size (H x V)	424 x 318 mm (16.7 x 12.5")
Aspect ratio (H:V)	4:3
Resolution	3MP (2048 x 1536)
Pixel pitch	0.2070 mm
Color imaging	No
Gray imaging	Yes
Number of grayscales (LUT in/LUT out)	1024 grey levels (10/10)
Viewing angle (H, V)	170°
Uniform Luminance Technology (ULT)	Yes
Per Pixel Uniformity (PPU)	No
Ambient Light Compensation (ALC)	No
Backlight Output Stabilization (BLOS)	Yes
I-Guard	No
Maximum luminance	1000 cd/m ²
DICOM calibrated luminance (ULT off)	500 cd/m ²
Contrast ratio (ULT off)	900:1
Response time (Tr + Tf)	50 ms
Video input signals	DVI-D Dual Link
USB ports	1 upstream, 2 downstream
USB standard	1.1
Power consumption (nominal)	54W
Power save mode	Yes
Dimensions with stand (W x H x D)	Portrait: 382 x 577~637 x 249 mm Landscape: 488 x 472~532 x 249 mm
Dimensions w/o stand (W x H x D)	Portrait: 382x 488 x 114 mm Landscape: 488 x 382 x 114 mm
Net weight with stand	11.5 kg
Mounting standard	VESA (100 mm)
Screen protection	Protective, non-reflective PMMA cover
Recommended modalities	CT, MR, US, DR, CR, NM, Film
Certifications	UL 60601-1 1ST EDITION, CAN/CSA-C22.2 NO. 601.1-M90, UL 60950-1 1ST EDITION, CSA C22.2 NO. 60950-1-03 1ST EDITION, IEC 60601-1 2ND ED:1988 + A1:1991 + A2:1995, IEC 60950-1:2001 1ST EDITION, CE - 2004/108/EC, CE - 93/42/EC, A1:2007/47/EC CLASS IIB, DEMKO - EN 60601-1, DEMKO - EN 60950-1, CCC - GB9254-1998 + GB4943-2001 + GB17625.1-2003, VCCI, FCC class B, BSMI, KETI, FDA 510K, Rohs
Supplied accessories	Getting Started Guide Quick-Installation Sheet Video cable (DVI Dual Link) Main cables (UK, European (CEBEC/KEMA), USA (UL/CSA; adaptor plug NEMA 5-15P), Chinese (CCC))
Optional accessories	NA
QA software	MediCal QAWeb

BARCO

Visibly yours

Warranty

5 years
